

2008-2010 FORD 6.4L POWERSTROKE
PLUG-N-PLAY MODULE

USER MANUAL

Disclaimer

- By installing this product onto your vehicle, you assume all risk and liability associated with its use.
- GDP Tuning, LLC. is not responsible for misuse of its products. By installing this product, you release GDP Tuning, LLC. of any and all liability associated with its use.
- The purchaser and end user releases, indemnities, discharges and holds harmless GDP Tuning, LLC. from any and all claims, damages, causes of action, injuries, or expenses resulting from or relating to the use or installation of this product that is in violation of the terms and conditions on this page, the product disclaimer, and/or the product installation instructions. GDP Tuning, LLC. will not be liable for any direct, indirect, consequential, exemplary, punitive, statutory, or incidental damages or fines caused by the use or installation of this product.

Caution

Never work on a hot vehicle. Serious injury in the form of burns can result if the vehicle has been in use. Allow vehicle to cool prior to installation. Always wear eye protection when working on or under any vehicle.

2008-2010 FORD 6.4L POWERSTROKE PLUG-N-PLAY MODULE

GDP231003



A. Plug-N-Play Module

B. Harness

Notice:

Make sure to disconnect the negative side battery terminal before beginning your install. Failure to do so may cause CEL's and lack of performance.

Step 1

Find a dry location to mount the GDP module using the supplied zip ties. We recommend an area that is away from moving parts and extreme heat.



Step 2

Locate the 15 pin connector found on the passenger side of engine. The fuel sensor signal and power wires are integrated into this connector.



Step 3

Disconnect the plug and connect our supplied connectors in-line.



Step 4

Route the switch wire through the firewall to the module. We recommend utilizing an existing grommet in the firewall and running the wire through there. Make sure not to cut any wires if you need to make a new hole in the firewall.

Step 5

Now you need to decide where you want to mount your adjustable switch. If you do not want to drill your dash, we have included our GDP switch bracket.

Step 6

Re-connect the battery terminals.